

# 75 Ω SCREW-ON TYPE CONNECTORS, ADAPTERS & TERMINATION



<p><b>8723-XX-*</b></p> <p><b>STRAIGHT FEMALE CABLE PLUG</b></p> <p>Clamp for Flexible Cable Solder/Clamp for Cable Groups 30 &amp; 31</p>	<p><b>8733-XX-*</b></p> <p><b>STRAIGHT FEMALE CABLE PLUG</b></p> <p>Crimp Type</p>	<p><b>8726-XX-*</b></p> <p><b>RIGHT ANGLE FEMALE CABLE PLUG</b></p> <p>Clamp for Flexible Cable Solder/Clamp for Cable Groups 30 &amp; 31</p>	<p><b>8736-XX-*</b></p> <p><b>RIGHT ANGLE FEMALE CABLE PLUG</b></p> <p>Crimp Type</p>
--	--	---	---

<p><b>8722-XX-*</b></p> <p><b>STRAIGHT MALE CABLE JACK</b></p> <p>Clamp for Flexible Cable Solder/Clamp for Cable Groups 30 &amp; 31</p>	<p><b>8732-XX-*</b></p> <p><b>STRAIGHT MALE CABLE JACK</b></p> <p>Crimp Type</p>	<p><b>8724-XX-*</b></p> <p><b>STRAIGHT MALE BULKHEAD CABLE JACK</b></p> <p>Clamp for Flexible Cable Solder/Clamp for Cable Groups 30 &amp; 31</p>	<p><b>8734-XX-*</b></p> <p><b>STRAIGHT MALE BULKHEAD CABLE JACK</b></p> <p>Crimp Type</p>
--	--	---	---

<p><b>8725-*</b></p> <p><b>STRAIGHT MALE CHASSIS JACK RECEPTACLE</b></p> <p>Nut in Front of Panel</p>	<p><b>8740-*</b></p> <p><b>STRAIGHT MALE CHASSIS JACK RECEPTACLE</b></p> <p>Nut in Back of Panel</p>	<p><b>8730-*</b></p> <p><b>STRAIGHT MALE RECEPTACLE PRINTED CIRCUIT</b></p>	<p><b>8731-*</b></p> <p><b>RIGHT ANGLE MALE RECEPTACLE PRINTED CIRCUIT</b></p>
---	--	---	--

**ADAPTERS AND TERMINATION**

<p><b>8728-*</b></p> <p><b>MALE TO MALE TO MALE</b></p> <p>Available with Offset Bracket Upon Request</p>	<p><b>8729-*</b></p> <p><b>FEMALE TO FEMALE TO FEMALE</b></p> <p>Available with Offset Bracket Upon Request</p>	<p><b>8811-*</b></p> <p><b>BULKHEAD MOUNTED STRAIGHT MALE JACK TO JACK ADAPTER</b></p>	<p><b>8705F-75-1</b></p> <p><b>FEMALE PLUG RESISTIVE TERMINATION (1/2 W, 5%)</b></p>
---	---	--	--

XX SEE NOTE ON SPECIFICATION SHEET FOR CABLE GROUPS, MATERIAL, FINISH CODES.  
\* 1 indicates gold plating, -7 indicates nickel plating. NOTE: Bulkhead models are designed for use with .093" max. thick panel.

<p>6743-XX-* / 6753-XX-*</p> <p><b>STRAIGHT FEMALE CABLE PLUG</b> 6743 Clamp Type 6753 Crimp Type</p> <p>For Crimp Style 11/32 hex</p> <p>Clamp for flexible cable Solder/Clamp for cable groups 30 &amp; 31</p>	<p>6746-XX-*</p> <p><b>RIGHT ANGLE FEMALE CABLE PLUG</b></p> <p>11/32 hex</p> <p>Clamp for flexible cable Solder/Clamp for cable groups 30 &amp; 31</p>	<p>6756-XX-*</p> <p><b>RIGHT ANGLE FEMALE CABLE PLUG</b></p> <p>Crimp Type</p>	<p>6744-XX-* / 6754-XX-*</p> <p><b>STRAIGHT MALE BULKHEAD CABLE JACK</b> 6744 Clamp Type 6754 Crimp Type</p> <p>For Crimp Style 11/32 hex</p> <p>Clamp for flexible cable Solder/Clamp for cable groups 30 &amp; 31</p>
--	---	--	---

<p>6742-XX-* / 6752-XX-*</p> <p><b>POSITIVE LOCKING CRIMP PLUGS</b></p>		
<p>6742-XX-* / 6752-XX-*</p> <p><b>STRAIGHT MALE CABLE JACK</b> 6742 Clamp Type 6752 Crimp Type</p> <p>For Crimp Style 11/32 hex</p> <p>Clamp for flexible cable Solder/Clamp for cable groups 30 &amp; 31</p>	<p>6753L-XX-* <b>STRAIGHT FEMALE</b></p> <p>11/32 hex</p> <p>5/16 hex</p> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>• RETRACTABLE SPRING COLLAR</li> <li>• VISUAL LOCKING STATUS</li> <li>• MATES WITH ANY STANDARD 75 OHM SNAP-ON JACK</li> <li>• AVAILABLE FOR CABLE GROUPS 24A, 25B</li> </ul>	<p>6756L-XX-* <b>RIGHT ANGLE FEMALE</b></p> <p>.72</p>

<p>6750-*</p> <p><b>STRAIGHT MALE RECEPTACLE PRINTED CIRCUIT</b></p> <p>.036 dia. .040 sq. (typ)</p>	<p>6751-*</p> <p><b>RIGHT ANGLE MALE RECEPTACLE PRINTED CIRCUIT</b></p> <p>.036 dia. .040 sq. (typ)</p>	<p>6745-*</p> <p><b>STRAIGHT MALE CHASSIS RECEPTACLE</b></p> <p>5/16-32 UNF-2A 3/8 hex</p> <p>Nut in Front of Panel</p>	<p>6760-*</p> <p><b>STRAIGHT MALE CHASSIS RECEPTACLE</b></p> <p>3/8 hex 5/16-32 UNF-2A</p> <p>Nut Behind Panel</p>
--	---	---	--

<p><b>ADAPTERS AND TERMINATION</b></p>			
<p>6748-*</p> <p><b>MALE TO MALE TO MALE</b></p> <p>Available with Offset Bracket upon Request</p>	<p>6749-*</p> <p><b>FEMALE TO FEMALE TO FEMALE</b></p> <p>Available with Offset Bracket upon Request</p>	<p>6820-*</p> <p><b>STRAIGHT MALE JACK TO JACK</b></p> <p>5/16-32 UNF-2A 3/8 hex</p> <p>Bulkhead Mounted</p>	<p>6705F-75-1</p> <p><b>FEMALE PLUG RESISTIVE TERMINATION (1/2 W, 5%)</b></p> <p>11/32 hex</p>

XX-\* SEE NOTE ON SPECIFICATION SHEET FOR CABLE GROUPS, MATERIAL, FINISH CODES.

\* 1 indicates gold plating, -7 indicates nickel plating. NOTE: Bulkhead models are designed for use with .093" max. thick panel.