

<p>014090-XX-4</p> <p>RIGHT ANGLE CABLE PLUG</p> <p>Crimp Type for Flexible Cable Solder Type for Cable Groups 30, 31 & 48A</p>	<p>014210-XX-4</p> <p>BULKHEAD CABLE JACK</p> <p>Clamp Type Use Mounting Hole A</p>	<p>014088-XX-4</p> <p>BULKHEAD CABLE JACK</p> <p>Crimp Type for Flexible Cable Solder Type for Cable Groups 30, 31 & 48A Use Mounting Hole B</p>	<p>014146-XX-*</p> <p>FLANGE MOUNT CABLE JACK</p> <p>Use Mounting Hole A</p>
<p>014038-XX-4</p> <p>MALE CLAMP PLUG</p> <p>Combination Straight or Right Angle</p>	<p>014039-XX-4</p> <p>MALE CRIMP PLUG</p> <p>Combination Straight or Right Angle</p>	<p>014215-*</p> <p>FLANGE MOUNT JACK RECEPTACLE</p> <p>Solder Cup • Use Mounting Hole D</p>	<p>014244-4</p> <p>FLANGE MOUNT JACK RECEPTACLE</p> <p>Blunt Post • Use Mounting Hole C</p>
<p>014111-4</p> <p>STRAIGHT MALE PANEL RECEPTACLE</p> <p>Use Mounting Hole D</p>	<p>014116-4</p> <p>FEMALE RIGHT ANGLE PANEL RECEPTACLE</p> <p>Use Mounting Hole C</p>	<p>014230-4</p> <p>MALE DUST CAP</p>	<p>014230F-4</p> <p>FEMALE DUST CAP</p>
<p>INTRA-SERIES ADAPTERS</p>			
<p>014218-4</p> <p>MALE TO MALE</p>	<p>014653-4</p> <p>FEMALE TO FEMALE</p>	<p>014085-4</p> <p>RIGHT ANGLE MALE TO MALE</p>	<p>014219-4</p> <p>RIGHT ANGLE MALE TO FEMALE</p>

SEE SPECIFICATION SHEET FOR CABLE GROUPS AND MOUNTING HOLE SIZE
NOTE: Bulkhead models are designed for use with .093" maximum thick panel.